

Mobil Delvac Super 1400 15W-40

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Super 1400 is a high performance diesel engine oil that provides proven protection of diesel engines operating in severe conditions for both on and off-highway applications.

Mobil Delvac Super 1400 15W-40 is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

The technology in Mobil Delvac Super 1400 15W-40 delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Component compatibility	Longer gasket and seal life

Applications

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

Mobil Delvac Super 1400 15W-40 has the following 15W-40 industry specifications

API CH-4	X
----------	---

Mobil Delvac Super 1400 15W-40 has the following 15W-40 builder approval

MB-Approval 228.3	X
-------------------	---

Mobil Delvac Super 1400 15W-40 recommended for use in applications requiring

API SJ	X
MAN M 3275	X



Mobil Delvac Super 1400 15W-40 recommended for use in applications requiring	15W-40
Volvo VDS-2	X

Typical Properties

Mobil Delvac Super 1400 15W-40	
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	107
cSt @ 100°C	14.7
Viscosity Index, ASTM D 2270	135
Sulfated Ash, wt%, ASTM D 874	1.1
Total Base #, mg KOH/g, ASTM D 2896	10.0
Pour Point, °C, ASTM D 97	-27
Flash Point, °C, ASTM D 92	244
Density @15 °C kg/l, ASTM D 4052	0.88

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, Delvac (and any other trademarks) are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.