

Mobil Super 1000 Turbospeed 15W-40

Premium Multigrade Diesel Engine Oil

Product Description

Mobil Super 1000 Turbospeed 15W-40 is a premium mineral motor oil that is specially designed to suit Thailand diesel powered pick ups providing a high level of performance and protection under everyday conditions.

Features and Benefits

Mobil Super 1000 products are industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 1000 Turbospeed 15W-40 is meticulously engineered for today's tougher engine specifications and provides:

- Improved soot handling and oxidation capability for excellent wear protection and engine cleanliness
- Improved engine quietness compared with lower viscosity oils

Applications

Mobil Super 1000 Turbospeed 15W-40 is suitable for nearly all diesel engine types including common rail, turbocharged and intercooler models. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Diesel engines in passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 1000 Turbospeed 15W-40 meets the following industry specifications:

API	CH-4/CG-4/CF-4
-----	----------------

Typical Properties

Mobil Super 1000 Turbospeed 15W-40

SAE Grade

Filling

Viscosity, ASTM D 445

cSt @ 40°C

107



Mobil Super 1000 Turbospeed 15W-40

cSt @ 100°C	14.7
Viscosity Index, ASTM D 2270	135
Sulfated Ash, wt%, ASTM D 874	1.1
Pour Point, °C, ASTM D 97	-27
Flash Point, °C, ASTM D 92	244
Density @15 °C kg/l, ASTM D 4052	0.88

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.